



## Ram Audio RAM AUDIO ZETTA 460 - PA Amplifier 4 x 1450W 2 Ohm

CARACTERISTIQUES GENERALES :	
------------------------------	--

Réf :	AH-RAMZ460
-------	------------



### Ram Audio RAM AUDIO ZETTA 460 - PA Amplifier 4 x 1450W 2 Ohm

The RAM Audio ZETTA Series, is the result of an in depth study, in order to reach the best compromise between economy and performances, taking advantage of latest improvements in automated mixed surface mount and through hole electronic assembly.ZETTA Series is a project based on an upside-down mono-block approach offering an all-in-one power module that contains the entire amplifier assembly. Simplicity and effectiveness run hand by hand through the entire design to obtain an effectively skilled and workable product.The last generation QuantaPulse? switching power supply allows to reach a new level of refined sensing and control of the power flow.The cost-effective ZETTA Series amplifiers are packed with solid and convincing arguments for the professionals researching quality, reliability and value!.

Unmatched audio quality hi efficiency Class H design2/4 Channels models from 1000W up to 10000WUltra light weight 6kg, compact package 25cm deepLast generation QuantaPulse? switch mode power supplyPower Management System (PMS?) and Clip Limiter (ICL?)Up-side-down design to avoid fan dust accumulationIndustry standard Neutrik® XLR and Speakon® connectorsComprehensive protection set (ICL, PMS, SSP, turn-on, Temp, DC?)Detented sealed potentiometersDual or bridge mode operationTemperature controlled, back to front cooling fan

Type de produitAmplificateursTypeAmplificateursPuissance de sortie sur 2 Ohms4 x 1450WPuissance de sortie sur 4 Ohms4 x 1500WPuissance de sortie sur 8 Ohms4 x 1100WPuissance de sortie (4 Ohms, mode Bridge)2 x 2900WPuissance de sortie (8 Ohms, mode Bridge)2 x 3000WHigh Z 70Vrms / 100Vpeak4 x 1500WHigh Z 100Vrms / 140Vpeak4 x 800WGamme de fréquence20Hz - 20kHzTaux de distorsion (THD)500Crosstalk (20Hz - 1kHz)>75dBAmplification d'alimentation (Gain)26 - 40 dBsensibilité SPL4,7 - 0,9VRapport signal/bruit106 dBtension secteur170 V AC - 265 V AC, 50 - 60 Hz, 90 V AC - 140 V AC, 50 - 60 Hz1/8 de la puissance nominale (@230V/4 ohm)15 ACircuits de protectionCharges ouvertes ou inadaptées, Court-circuit, DC, ICL?, Mute à la mise sous tension, PMS?, protection contre les transitoires à l'allumage/extinction, RF, SSP?, Surcharge du bloc secteur, Surchauffe,



PROZIC  
113 Ancienne route Imperiale  
31120 Portet-sur-Garonne

05 82 050 710

Temporisation au démarrage Largeur 483 mm Hauteur (mm) 89 mm Profondeur 320 mm Poids 6 Kg EAN : 4049521619038

Packaging :

Dimensions produit :	483mm	Poids : 6Kg	EAN : 4049521619038
<i>Données non contractuelles</i>			