

Eminence Delta - Haut-parleur 15 Pouces 400W 8 Ohms**CARACTERISTIQUES GENERALES :**

Réf : ED15A

Eminence Delta - Haut-parleur 15 Pouces 400W 8 Ohms

Série DELTA-15A Standard American Recommandé pour les applications audio professionnelles, en tant que boomer/médium, ou pour retour de scène optimisé pour les voix, en coffret clos. Donne également de bons résultats en tant que boomer/médium ou boomer en coffret bass reflex.

SPECIFICATION

Nominal Basket Diameter 15", 381 mm

Nominal Impedance 8 ohms

Power Rating Watts 400 W / Music

Program 800 W Resonance 40 Hz

Usable Frequency Range 48 Hz - 4 kHz

Sensitivity 100 Magnet Weight 56 oz.

Gap Height 0.375", 9.53 mm

Voice Coil Diameter 2.5", 63.5 mm

THIELE & Small Parameters

Resonant Frequency (fs) 40 Hz DC

Resistance (Re) 6.3

Coil Inductance (Le) 0.64 mH

Mechanical Q (Qms) 8.05

Electromagnetic Q (Qes) 0.57

Total Q (Qts) 0.53

Compliance Equivalent Volume (Vas) 270.7 liters / 9.56 cu.ft

Peak Diaphragm Displacement Volume (Vd) 233 cc



PROZIC
113 Ancienne route Imperiale
31120 Portet-sur-Garonne
05 82 950 710

Mechanical Compliance of Suspension (Cms) 0.26 mm/N BL

Product (BL) 13.2 T-M

Diaphragm Mass inc. Airload (Mms) 62 grams

Efficiency Bandwidth Product (EBP) 70

Maximum Linear Excursion (Xmax) 2.7 mm

Surface Area of Cone (Sd) 864.6 cm²

Maximum Mechanical Limit (Xlim) 11.1 mm

MOUNTING Information

Recommended Enclosure Volume Sealed 37-42.5 liters/1.3-1.5 cu.ft.

Vented 82-161.4 liters/2.9-5.7cu.ft.

Overall Diameter 15.15", 384.8 mm

Baffle Hole Diameter 13.77", 349.6 mm

Front Sealing Gasket fitted as standard

Rear Sealing Gasket fitted as standard

Mounting Holes Diameter 0.25", 6.4 mm

Mounting Holes B.C.D. 14.56", 369.9 mm

Depth 6.05", 154 mm

MATERIALS of Construction Aluminum voice coil

Polyimide former Ferrite magnet

Vented core

Pressed steel basket

Paper Cone

Cloth cone edge

Solid composition paper dust cap

Packaging :

Dimensions produit :	155mm X Ø 385mm	Poids : 6Kg	EAN : 4049521025105
----------------------	-----------------	-------------	---------------------

Données non contractuelles